TANK CLEANER
ERW



- Electric drive
- RW angle head
- 270° jet coverage
- Up to 250 bar and 50 LPM

- Head and nozzles rotate about two axes
- Insertion opening larger than Ø 68 mm (automatic Ø 84 mm)
- 2 nozzles, 0°, 5° or 15° as required
- Drive with 11.9, 15.2 or 22 rpm
- Voltage 230 V, 115 V or 24 V AC
- Connecting pipe 500 to 4000 mm
- Cover made of plastic or stainless steel
- Up to 120 °C, stainless steel 1.4301
- Very low operating noise

The ERW is a tank cleaner with electric drive for the internal cleaning of production, storage and transport containers. It consists of the RW cleaning head, an electric drive and a connecting pipe. The RW angle head has an angled spray head rotating in three dimensions with a jet coverage of 270°. Its gears are fully mechanically encapsulated to protect them against contamination and damage. It is used for the partial internal cleaning of production and transport containers as well as storage tanks.


The drive motor sets the spray head in rotation. A toothing on the spray head engages with a fixed toothing on the connecting pipe, so that the spray head also rotates about a second axis offset by 90°. Thanks to the rotation about two axes, the nozzles cover an area of 270°.

The drive is available with 11.9, 15.2 or 22 rpm, and connecting pipes of different lengths adapt the cleaner to different tank sizes. Thanks to the modular design, the individual components can be replaced, so the unit is quickly ready for use again after servicing. The ERW is designed for durability, is easy to maintain and runs very quietly.

Technical data

Drive:	Electric motor
Speed:	11.9 / 15.2 / 22 rpm
Cleaning head:	RW (spray head combination S-RW-55)
Working pressure:	100 – 250 bar (1450 – 3625 psi)
Flow rate:	10 – 50 LPM (2.6 – 13.2 US gpm)
Max. temperature:	120 °C (248 °F)
Jet coverage:	270°
Nozzles:	2 pcs., 0° / 5° / 15°, 1/8"
Cleaning cycle:	depending on speed and degree of soiling
Connection:	M22 × 1.5 / G 1/2" / G 3/8"
Insertion opening:	larger than Ø 68 mm (2.68 inch); larger than Ø 84 mm (3.31 inch) with automatic extension/retraction
Connecting pipe:	Ø 35 mm (1.38 inch), length 500 – 4000 mm (19.7 – 157.5 inch)
Material head and pipe:	stainless steel 1.4301
Material drive:	PA6 black / stainless steel 1.4301
Seals:	FPM (Viton®) / EPDM / FDA
Item no.:	ERW.STD

Application example: cleaning an IBC



Variants

Cleaning time:	for a complete spray pattern approx. 4.6 / 3.6 / 2.5 min (at 11.9 / 15.2 / 22 rpm)
Voltage:	230 V AC 50 Hz, 115 V AC 60 Hz, 24 V AC
Cover:	plastic or stainless steel
Switch:	with or without switch
Cable gland:	rear or side
Connecting pipe:	500, 700, 1000, 1500, 2000, 3000, 4000 mm; other lengths on request


Maintenance


Nozzle cleaning:	with compressed air; for stubborn dirt, with a very thin metal rod
Nozzle replacement:	if required, with nozzles of the same type with identical nozzle opening
Maintenance interval:	approx. every 300 operating hours; replace all seals
Ball bearings:	replace with original bearings after 2,000 operating hours at the latest

The data, technical data and information presented do not release the user from the obligation to check the suitability of the products supplied for the intended application. All information is without guarantee. (Status: 01.10.2026) · Page 1/2


Components and dimensions


Dimensions in mm





Minimum installation opening in mm






1 Spray head combination S-RW-55
2 Connecting pipe Ø 35 mm
3 Electric drive
4 Nozzles

Length A	500 mm	700 mm	1000 mm	1500 mm	2000 mm	3000 mm	4000 mm
Item no.	**ER-W-0500**	**ER-W-0700**	**ER-W-1000**	**ER-W-1500**	**ER-W-2000**	**ER-W-3000**	**ER-W-4000**

Accessories and spare parts



Protective cage



Screw-in holder M64 × 4



Bunghole holder



Suspension bracket



Double handle



Nozzles




Stainless steel cover



Adapters M22 / M24 / NPT / 1/2"



Mounting flange



Barrel holder M64 × 4 / 2"



Sealing plug

Spare parts:	nozzles 0° / 5° / 15° (1/8"), seal kits, ball bearings, spray head combination S-RW-55
Further accessories:	screw connections M48 × 1.5, M64 × 4 and 2"; anything else on request
Documentation:	operating instructions, spare parts overview, certificates, declaration of conformity

Safety instructions

- The tank cleaner is suitable exclusively for cleaning the inside of production, storage and transport tanks that may be treated with a high-pressure water jet with cleaning solution.
- The unit may only be operated with fresh water and with cleaning agents expressly approved by the manufacturer. The operating conditions and performance limits stated in this data sheet must be observed.
- The unit is technical work equipment and is not intended for private use. Intended use also includes proper transport and professional storage.
- The maintenance intervals depend on the operating time, pressure range, media temperature and cleaning agent used and must be determined individually during trial operation. The operator is responsible for observing the maintenance intervals.

The data, technical data and information presented do not release the user from the obligation to check the suitability of the products supplied for the intended application. All information is without guarantee. (Status: 01.10.2026) · Page 2/2